



Printed board layout (1,6±0,2 thick)
View component side
(PCB plating = Tin)

Mounting force on Printed board : 25 - 80 N

| | | | | | | | | | | | | | | | | | | | | | | | |
|-------------------------------|----------------|------------|--------------------------------------|-------|-----------|--|---|---------------------------|------------------|------|---------|-----------|----|-------|--|--|--------|--|--|---|--|--|-------------------|
| | | | | | | <table border="1"> <tr> <td></td> <td>Dat.</td> <td>Name</td> </tr> <tr> <td>Detail.</td> <td>26-OCT-01</td> <td>JB</td> </tr> <tr> <td>Insp.</td> <td></td> <td></td> </tr> <tr> <td>Stand.</td> <td></td> <td></td> </tr> </table> | | | Dat. | Name | Detail. | 26-OCT-01 | JB | Insp. | | | Stand. | | |  | | D-Sub male standard 15 poles with solder pins, screw-lock, board lock and grounding pins | Maßstab/ Scale |
| | Dat. | Name | | | | | | | | | | | | | | | | | | | | | |
| Detail. | 26-OCT-01 | JB | | | | | | | | | | | | | | | | | | | | | |
| Insp. | | | | | | | | | | | | | | | | | | | | | | | |
| Stand. | | | | | | | | | | | | | | | | | | | | | | | |
| | | | All Dim. in mm Orig. Size DIN A 4 | | 1,5:1 | | | | | | | | | | | | | | | | | | |
| A | 09 66 262 6813 | 4-40 UNC | 2 | | | | | | | | | | | | | | | | | | | | |
| | 09 66 262 7813 | 4-40 UNC | 3 | | | | | | | | | | | | | | | | | | | | |
| | 09 66 262 5813 | 4-40 UNC | 0,76 µm Au | 29725 | 26-OCT-01 | JB | | | | | | | | | | | | | | | | | |
| | Part number | screw-lock | Performance level | Mod. | Dat. | Name | | | | | | | | | | | | | | | | | |
| HARTING EURL F-95972 Paris | | | | | | |  | TB 09 66 262 X81X Sub. | Blatt/ Page 3 | | | | | | | | | | | | | | |