



|  |             |
|--|-------------|
| VDC                                    | 1200 V      |
| Q <sub>C</sub>                         | 129/258 nC* |
| I <sub>F</sub> (T <sub>C</sub> <135°C) | 30/60 A*    |

\*Per Leg/Device

**Amp+™ Features**


- High surge current capable
- Zero reverse recovery current
- High bandwidth
- Fast, temperature-independent switching

**Amp+™ Benefits**


- Unipolar rectifier
- Zero switching loss
- Higher efficiency
- Smaller heat sink
- Parallel devices with thermal stability

**Amp+™ Applications**

- Motor drives
- Switch mode power supplies
- Power factor correction



| Part #       | Package   | Marking     |
|--------------|-----------|-------------|
| GP2D060A120U | TO-247-3L | GP2D060A120 |



| Maximum Rating Per Leg                             | Symbol                                | Conditions                                     | Value     | Unit             |
|--|---------------------------------------|--|-----------|------------------|
| Continuous forward current                         | I <sub>F</sub>                        | T <sub>C</sub> =25 °C, T <sub>J</sub> =175 °C  | 94        | A                |
|  |                                       | T <sub>C</sub> =125 °C, T <sub>J</sub> =175 °C | 52        |                  |
|  |                                       | T <sub>C</sub> =150 °C, T <sub>J</sub> =175 °C | 35        |                  |
| Surge non-repetitive forward current sine halfwave | I <sub>F,SM</sub>                     | T <sub>C</sub> =25 °C, t <sub>p</sub> =8.3 ms  | 240       | A                |
|  |                                       | T <sub>C</sub> =150 °C, t <sub>p</sub> =8.3 ms | 150       |                  |
| Non-repetitive peak forward current                | I <sub>F,max</sub>                    | T <sub>C</sub> =25 °C, t <sub>p</sub> =10 μs   | 600       | A                |
| i <sup>2</sup> t value                             | ∫i <sup>2</sup> dt                    | T <sub>C</sub> =25 °C, t <sub>p</sub> =8.3 ms  | 239       | A <sup>2</sup> s |
|  |                                       | T <sub>C</sub> =150 °C, t <sub>p</sub> =8.3 ms | 93        |                  |
| Repetitive peak reverse voltage                    | V <sub>RRM</sub>                      | T <sub>J</sub> =25 °C                          | 1200      | V                |
| Diode dv/dt ruggedness                             | dv/dt                                 | Turn-on slew rate, repetitive                  | 50        | V/ns             |
| Power dissipation                                  | P <sub>tot</sub>                      | T <sub>C</sub> =25 °C                          | 500       | W                |
| Operating & storage temperature                    | T <sub>J</sub> , T <sub>storage</sub> | Continuous                                     | -55...175 | °C               |
| Soldering temperature                              | T <sub>solder</sub>                   | Wave soldering leads                           | 260       | °C               |
| Mounting torque                                    |                                       | M3 Screw                                       | 1         | N-m              |

**Electrical Characteristics**, at T<sub>J</sub>=25 °C, unless otherwise specified

| Static Characteristics Per Leg | Symbol          | Conditions                                     | Values |      |      | Unit |
|--------------------------------|-----------------|--|--------|------|------|------|
|                                |                 |  | min.   | typ. | max. |      |
| DC blocking voltage            | V <sub>DC</sub> | I <sub>R</sub> =0.1mA                          | 1200   | -    | -    | V    |
| Diode forward voltage          | V <sub>F</sub>  | I <sub>F</sub> =30A, T <sub>J</sub> =25 °C     | -      | 1.6  | 1.8  | V    |
|                                |                 | I <sub>F</sub> =30A, T <sub>J</sub> =175 °C    | -      | 2.2  | 2.7  |      |
| Reverse current                | I <sub>R</sub>  | V <sub>R</sub> =1,200V, T <sub>J</sub> =25 °C  | -      | 5.0  | 500  | μA   |
|                                |                 | V <sub>R</sub> =1,200V, T <sub>J</sub> =175 °C | -      | 170  | 1000 |      |

# 1200V SiC Schottky Diode

Amp+™

GP2D060A120U

| Parameter | Symbol | Conditions | Values |      |      | Unit |
|-----------|--------|------------|--------|------|------|------|
|           |        |            | min.   | typ. | max. |      |

### AC Characteristics Per Leg

|                         |       |  |   |      |     |    |
|-------------------------|-------|--|---|------|-----|----|
| Total capacitive charge | $Q_C$ | $V_R=1,200V, T_j=25^\circ C$               | - | 129  | -   | nC |
| Switching time          | $t_c$ | $di_F/dt=200 A/\mu s$<br>$T_j=150^\circ C$ | - | -    | <10 | ns |
| Total capacitance       | C     | $V_R=1 V, f=1 MHz$                         | - | 1905 | -   | pF |
|                         |       | $V_R=600V, f=1 MHz$                        | - | 111  | -   |    |
|                         |       | $V_R=1,200V, f=1 MHz$                      | - | 108  | -   |    |

### Thermal Characteristics Per Leg

|                                   |            |                        |   |      |   |              |
|-----------------------------------|------------|------------------------|---|------|---|--------------|
| Thermal resistance, junction-case | $R_{thJC}$ | Package (flange) mount | - | 0.30 | - | $^\circ C/W$ |
|-----------------------------------|------------|------------------------|---|------|---|--------------|

### Typical Performance Per Leg

Fig. 1 Forward Characteristics (parameterized on  $T_j$ )




Fig. 2 Reverse Characteristics (parameterized on  $T_j$ )




Fig. 3 Power Derating




Fig. 4 Current Derating




Fig. 5 Capacitance






Fig. 6 Recovery Charge



Package Dimensions

Package TO-247-3L



| SYMBOL | MIN      | NOM   | MAX   |
|--------|----------|-------|-------|
| A      | 4.83     | 5.02  | 5.21  |
| A1     | 2.29     | 2.41  | 2.54  |
| A2     | 1.91     | 2.04  | 2.16  |
| b      | 1.14     | 1.27  | 1.40  |
| b1     | 1.91     | 2.10  | 2.20  |
| b2     | 2.92     | 3.10  | 3.20  |
| c      | 0.61     | 0.71  | 0.80  |
| D      | 20.80    | 21.07 | 21.34 |
| D1     | 17.43    | 17.63 | 17.83 |
| E      | 15.75    | 15.94 | 16.13 |
| E1     | 13.06    | 13.26 | 13.46 |
| E2     | 4.32     | 4.58  | 4.83  |
| e      | 5.45 BSC |       |       |
| L      | 19.81    | 20.19 | 20.57 |
| L1     | 3.81     | 4.07  | 4.32  |
| eP     | 3.55     | 3.60  | 3.65  |
| Q      | 5.59     | 5.90  | 6.20  |
| S      | 6.15 BSC |       |       |

**NOTE**  
1. THESE DIMENSION DO NOT INCLUDE MOLD PROTRUSION

**Note**

**RoHS Compliance**

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented March, 2013. RoHS Declarations for this product can be obtained from the Product Documentation sections of [www.gptechgroup.com](http://www.gptechgroup.com).

**REACH Compliance**

REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact our office at GPTG Headquarters in Lake Forest, California to insure you get the most up-to-date REACH SVHC Declaration. REACH banned substance information (REACH Article 67) is also available upon request.

This product has not been designed or tested for use in, and is not intended for use in, applications implanted into the human body nor in applications in which failure of the product could lead to death, personal injury or property damage, including but not limited to equipment used in the operation of nuclear facilities, life-support machines, cardiac defibrillators or similar emergency medical equipment, aircraft navigation or communication or control systems, or air traffic control.

Global Power Technologies Group Inc., Reserves the right to make changes to the product specifications and data in this document without notice.