

ECL SMD Aluminum Capacitor



KEY BENEFITS

- Polarized SMD aluminum electrolytic capacitors, non solid electrolyte
- Extra low impedance, high ripple current
- Temperature up to 105 °C
- Miniaturized
- SMD technology for high mounting density

APPLICATIONS

- Industrial and professional applications
- General industrial, consumer
- Smoothing, filtering, buffering

RESOURCES

- Datasheet: ECL - <http://www.vishay.com/doc?25020>
- For technical questions contact aluminumcaps2@vishay.com
- Material categorization: For definitions of compliance please see <http://www.vishay.com/doc?99912>




RoHS
COMPLIANT

One of the World's Largest Manufacturers of
Discrete Semiconductors and Passive Components



ECL SMD Aluminum Capacitor



QUICK REFERENCE DATA		
DESCRIPTION	UNIT	VALUE
Nominal case size (Ø D x L)	mm	6 x 5.8 to 12.5 x 13.5
Rated capacitance range C _R	µF	10 to 1500
Capacitance tolerance	%	± 20
Rated voltage range	V	6.3 to 50
Category temperature range	°C	- 40 to 105
Load life	h	2000
Based on sectional specification		IEC 60384-4/ EN 130300
Climatic category IEC 60068		40/105/56

PACKAGING

- Supplied in blister tape

ELECTRICAL DATA	
SYMBOL	DESCRIPTION
U _R	rated voltage
C _R	rated capacitance at 120 Hz
tan δ	max. dissipation factor at 120 Hz
R _{ESR}	max. equivalent series resistance at 120 Hz
I _R	rated alternating current at 120 Hz and upper category temperature
Z	max. impedance at 100 kHz

Note

Unless otherwise specified, all electrical values apply at T_{amb} = 20 °C, P = 86 to 100 kPa, RH = 45 to 75 %.

ORDERING EXAMPLE

ECL 22 µF/50 V, ± 20 %, size 6.3 x 5.8 mm

Ordering code: MALSECL00AD222HARK

For Standard Packaging Quantity (SPQ) and Minimum Order Quantity (MOQ) please refer to our price list or contact customer service.

SELECTION CHART FOR C _R , U _R AND RELEVANT NOMINAL CASE SIZES (Ø D x L in mm)						
C _R (µF)	RATED VOLTAGE (V)					
	6.3	10	16	25	35	50
10	→	→	→	→	→	6.3 x 5.8
22	→	→	→	→	→	6.3 x 5.8
33	→	→	→	→	6.3 x 5.8	8 x 6.2
47	→	→	→	→	6.3 x 5.8	8 x 6.2
68	→	→	→	6.3 x 5.8	8 x 6.2	8 x 10
100	→	→	6.3 x 5.8	8 x 6.2	8 x 10	10 x 10
220	6.3 x 5.8	6.3 x 7.7	8 x 6.2	8 x 10	10 x 10	-
330	8 x 6.2	→	8 x 10	-	-	-
470	→	8 x 10	10 x 10	-	-	-
680	→	10 x 10	-	-	-	-
1000	10 x 10	-	-	-	-	-
1500	10 x 10	-	-	-	-	-

ELECTRICAL DATA AND ORDERING INFORMATION							
U _R (V)	C _R 120 Hz (µF)	DIMENSIONS D x L (mm)	tan δ 120 Hz	Z 100 kHz/ 20 °C (Ω)	I _R 100 kHz/ 105 °C (mA)	WEIGHT (g)	CATALOG NUMBER
6.3	220	6.3 x 5.8	0.24	0.44	230	0.30	MALSECL00AD322BARK
	330	8 x 6.2	0.24	0.26	300	0.55	MALSECL00AE333BARK
	1000	10 x 10	0.24	0.09	670	1.21	MALSECL00AG410BARK
	1500	10 x 10	0.24	0.09	670	1.21	MALSECL00AG415BARK
10	220	6.3 x 7.7	0.19	0.34	280	0.40	MALSECL00BM322CARK
	470	8 x 10	0.19	0.17	450	1.00	MALSECL00AF347CARK
	680	10 x 10	0.19	0.09	670	1.21	MALSECL00AG368CARK
16	100	6.3 x 5.8	0.16	0.44	230	0.30	MALSECL00AD310DARK
	220	8 x 6.2	0.16	0.26	300	0.55	MALSECL00AE322DARK
	330	8 x 10	0.16	0.17	450	1.00	MALSECL00AF333DARK
	470	10 x 10	0.16	0.09	670	1.21	MALSECL00AG347DARK
25	68	6.3 x 5.8	0.14	0.44	230	0.30	MALSECL00AD268EARK
	100	8 x 6.2	0.14	0.26	300	0.55	MALSECL00AE310EARK
	220	8 x 10	0.14	0.17	450	1.00	MALSECL00AF322EARK
35	33	6.3 x 5.8	0.12	0.44	230	0.30	MALSECL00AD233FARK
	47	6.3 x 5.8	0.12	0.44	230	0.30	MALSECL00AD247FARK
	68	8 x 6.2	0.12	0.26	300	0.55	MALSECL00AE268FARK
	100	8 x 10	0.12	0.17	450	1.00	MALSECL00AF310FARK
	220	10 x 10	0.12	0.09	670	1.21	MALSECL00AG322FARK
50	10	6.3 x 5.8	0.12	0.88	165	0.30	MALSECL00AD210HARK
	22	6.3 x 5.8	0.12	0.88	165	0.30	MALSECL00AD222HARK
	33	8 x 6.2	0.12	0.63	300	0.55	MALSECL00AE233HARK
	47	8 x 6.2	0.12	0.63	300	0.55	MALSECL00AE247HARK
	68	8 x 10	0.12	0.34	450	1.00	MALSECL00AF268HARK
	100	10 x 10	0.12	0.18	670	1.21	MALSECL00AG310HARK

Revision 12-Dec-08