


WIRING INFORMATION

	J1	Wire color	J2
⌘	2-e	Rose	2-e
	1-e	Orange	1-e
⌘	2-d	Yellow	2-d
	1-d	Rose	1-d
⌘	2-c	Rose	2-c
	1-c	Brown	1-c
⌘	2-b	Black	2-b
	1-b	Rose	1-b
⌘	2-a	Rose	2-a
	1-a	Red	1-a
	Shell	Braid	Shell



33 27 243 350 0029	3.5 m
33 27 243 400 0028	4 m
33 27 243 300 0027	3 m
33 27 243 060 0026	0.6 m
33 27 242 100 0021	10 m
33 27 243 800 0020	8 m
33 27 243 650 0019	6.5 m
33 27 243 200 0003	2 m
33 27 243 100 0002	1 m
33 27 243 050 0001	0.5 m
<i>Part-No.</i>	<i>Dim. L</i>

NOTES /

- CABLE ASSEMBLY IS MANUFACTURED PER RELEVANT JOB.
- MECHANICAL REQUIREMENTS
 - OPERATING TEMPERATURE = -20° TO +105°C
 - MATING CYCLES : 250, PERFORMANCE LEVEL 2 (IEC 60512-5)
- THE CONNECTOR COMPLIES REQUIREMENT : IEC 61076-4-107
- WHITE LABEL INFORMATION:

DATE CODE & LOT INFORMATION
 HARTING P/N
- CABLE MUST BE PERFORMED HI-POT TEST AND CONTINUITY TEST
- CABLE MUST BE PACKED INTO A PLASTIC BAG.

	All Dimensions in mm Original Size DIN A 3			Techn. Character.			Free size tolerances		
				Det.	Name	Scale	Har-link standard cable, male IDC double ended		
				Detail.	4.03.09				P.D.
				Insp.					
			Stand.						
Mod.	Dat.	Name	ZHUHAI HARTING LIMITED				TB 33 27 24x xxx 00xx		
							Sub.	Page	