



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. CONTACT RATING: 50mA @ 12VDC
 4. CONTACT RESISTANCE: 100mΩ MAX.
 5. INSULATION RESISTANCE: 100MΩ MIN @ 500VDC.
 - ▲ 6. OPERATING FORCE: 185 ± 50gf
 7. TRAVEL: 0.15 mm
 8. OPERATING TEMPERATURE: -25°C TO + 70°C
 9. OPERATING LIFE: 200,000 CYCLES
 - ▲ 10. CONTACTS: SILVER
 11. ▲ DENOTES CRITICAL PARAMETERS
 12. 2002/95/EC (ROHS) COMPLIANT
 13. PARTS TO BE PACKAGED IN TAPE AND REEL

C	21965	UPDATE TO GRAY ACTUATOR	8/25/2015	MW
B	21887	update drawing	6/15/15	rc
A	21236	New Release	9/16/13	rc
REV	PCR NO	DESCRIPTION	DATE	BY



TITLE TL3360AF185Q				
SCALE 4:1	DATE 9/16/2013	DR rc	DWG N330000	REV C

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED