


2400-2500 MHz RADOME OMNI – 8 dBi

OMNIDIRECTIONAL ANTENNA

RO2408NM

Series : ANTENNA



All dimensions are in inches

Issue : 0816

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

2400-2500 MHz RADOME OMNI – 8 dBi**OMNIDIRECTIONAL ANTENNA****RO2408NM**

Series : ANTENNA

ELECTRICAL SPECIFICATIONS

Frequency :.....	2400-2500 MHz
Nominal Impedance :.....	50 Ω
VSWR :.....	2:1 Max
Gain :.....	8 dBi
Radiation Pattern	
-3 dB beamwidth	
Horizontal Plane :	Omni
Vertical Plane :	14 ° ± .5 °
Cross Polarization level	
Horizontal Plane :	>23 dB
Vertical Plane :	>23 dB
Polarization :	VERTICAL
Power withstanding :.....	20 W
Connector type :	N Male

MECHANICAL SPECIFICATIONS

Radome :	Pultruded Fiberglass, UV-Protected
Plastic cap :	Acrylonitrile Styrene Acrylate (ASA) UL File-N°. E41871 (UL 94 – HB)
Adhesive :.....	3M Scotch Weld™ DP-190 Gray
Color :.....	WHITE
Ingress Protection :.....	IP 67
Weight :.....	6.4 oz
Wind-loading :	150 Mph
Side-loading @ 1ft :.....	30 lbs
Vertical Pull :	100 lbs
Overall length :	20.31 INCHES

Issue : 0816

In the effort to improve our products, we reserve the right to make changes judged to be necessary.



2400-2500 MHz RADOME OMNI – 8 dBi**OMNIDIRECTIONAL ANTENNA****RO2408NM**

Series : ANTENNA

ENVIRONMENTAL SPECIFICATIONS

Temperature:	-40/+65 ° C
Ingress Protection :.....	IP 67
Temperature Cycling:.....	-40°C dwell 6 hours/+65°C dwell 6 hours 4 full cycles (no condensation)
Leak Test:.....	Fully submerged 12” 12 hours (no water intrusion)

OTHER SPECIFICATIONS**Issue : 0816**

In the effort to improve our products, we reserve the right to make changes judged to be necessary.







2400-2500 MHz RADOME OMNI – 8 dBi

OMNIDIRECTIONAL ANTENNA

RO2408NM

Series : ANTENNA

CURVES



Issue : 0816

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

