



PERFORMANCE CHARACTERISTICS

- CURRENT RATING: 1.5 A AT 20°C (FULLY LOADED)
- 1 A AT 70°C (FULLY LOADED)
- RATED VOLTAGE: 500 V AC (CONT /CONT)
- OPERATING TEMPERATURE : -55°C TO 125°C
- CONTACT RESISTANCE : 20 m Ω MAX
- INSERTION FORCE: 0.75N MAX/CONT
- EXTRACTION FORCE : 0.15N MIN /CONT
- INSULATION RESISTANCE: 10⁴ MΩ MIN

NOTES

1. LEAD FREE INDICATOR :LF=LEAD FREE
2. THIS PRODUCT IS CSA APPROVED.
THIS PRODUCT IS UL RECOGNIZED.
3. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING :BS.A.201572.001
4. THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

Material		Spec ref	
Mat code		✓	TOLERANCE
Heatreat			1DEC ±0.2 1DEC
Plating/Finish			2DEC ±0.1 2DEC
			ANGLES ±1°HÖEKEN
Dr	10 2 92	J.V.B	size
Eng			A1
Chr			Scale
Appr			5.000
Product family		Model Name	
Model Revision		REL Level	
MPACS 5+2R RA		BS.C .201444.002	
RCP CONN TYPE B		Rev. E	
Pro/E file	CAT.NO. HM2R02PA5101----	CUSTOMER DRAWING	
sheet 1 of 1			

This drawing is the property of FC. It is to be used only for the purpose intended. No part of this drawing may be reproduced without the written permission of FC. Copyright © FC.