

RG6/U Quad-Shield CMR-Rated Coaxial Cable, White, 1000 ft.

MODEL NUMBER: **A224-01K-WH**



Premium coaxial cabling designed for high-frequency indoor/outdoor applications, such as television antennas, digital cable and satellite transmissions, and video surveillance systems.

Description

The A224-01K-WH RG6/U Quad-Shield CMR-Rated Coaxial Cable is premium cabling designed for high-frequency indoor/outdoor applications, such as television antennas, digital cable and satellite transmissions, and video surveillance systems. RG6/U coaxial cable has lower attenuation than RG59 cable, making it superior over long distances.

Manufactured with an 18 AWG copper-clad steel center conductor, the 75-ohm A224-01K-WH is tested to 3 GHz and features quad shielding, which means aluminum foil and braid shielding over another layer of aluminum foil and braid for error-free transmission. Protected by a flame-retardant CMR-rated PVC jacket, this white cable meets UL1655, UL13, UL444 and RoHS standards.

Features

Coaxial Cabling for High-Frequency Indoor/Outdoor Applications

- Ideal for television antennas, digital cable and satellite transmissions, and video surveillance systems
- White 75-ohm cable tested to 3 GHz
- Lower attenuation than RG59 cable for longer distances

Premium Construction for Superior Performance

- 18 AWG copper-clad steel center conductor
- Quad foil and braid shielding for error-free transmission
- Flame-retardant CMR-rated PVC jacket
- Meets UL1655, UL13, UL444 and RoHS standards

Highlights

- Lower attenuation than RG59 cable for longer distances
- 18 AWG copper-clad steel center conductor
- Quad foil and braid shielding for error-free transmission
- Flame-retardant CMR-rated PVC jacket
- Meets UL1655, UL13, UL444 and RoHS standards

Package Includes

- A224-01K-WH RG6/U Quad-Shield CMR-Rated Coaxial Cable, White, 1000 ft.



TAA-Compliant

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
UPC Code	037332196415
Technology	Coax; RG59/RG6
INPUT	
Cable Length (ft.)	1000
Cable Length (m)	304.8
PHYSICAL	
Shipping Dimensions (hwd / in.)	9.450 x 20.870 x 20.870
Shipping Dimensions (hwd / cm)	24.00 x 53.01 x 53.01
Shipping Weight (lbs.)	35.0000
Shipping Weight (kg)	15.88
Color	White
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>