



NOTES:

1. METALSHELLS: STEEL; min. 320µ" TIN
2. INSULATORS: PBT GF UL 94 V-0, BLACK
3. THREADED INSERT: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL
4. COLLAR: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL
5. MAXIMUM TORQUE VALUE FOR THREAD: 6" LBS
6. = CRITICAL DIMENSION
7. CONNECTOR IS PART MARKED: PART NO: CONEC Y/WW

Directive 2002/95/EC
RoHS
Compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND		tolerance		scale: 2:1	material: SEE NOTES	
	rev.	description	date	name	D-SUB COMBINATION MALE CRIMP STYLE 17W2P with threaded insert	
			2001	date		name
			drawn	17.05.		Parei
			appd.	17.05.		Mickenbecker
		norm			title:	
		d-old			dwg no: AutoCAD 2000	
					DIN-A	
					13K1A251A	
					sh: 1/1	
					part no: 3017W2P XK99A30X	

