

Specification Sheet

Part Number: 596-00816

VOLTAJE NOMINAL DE OPERACIÓN DE CA	<input type="text"/>
FRECUENCIA NOMINAL DE OPERACIÓN DE CA	<input type="text"/>
POTENCIA MÁXIMA DE CA	<input type="text"/>
CORRIENTE MÁXIMA DE CA	<input type="text"/>
SOBRECORRIENTE NOMINAL MÁXIMA DEL DISPOSITIVO PARA PROTECCIÓN DEL MODULO DE CA	<input type="text"/>

Article Number

596-00816

Type

AC2011S

Color

Red (RD)

Features & Benefits

- Made with UV-stable inks and materials for durability and weather resistance.
- Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.
- High abrasion and scuff resistance for high-performance labeling.
- Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Quantity Per

roll

Product Description

HellermannTyton pre-printed Solar Rating labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description

Solar Label, Printable, Spanish, AC MODULE, 4.0" x 2.0", PET, Red, 50/roll

Global Part Name

AC2011S-840/926-RD

Technical Description

Printable Solar Label, Spanish Version, AC MODULE LABEL, 4.0" X 2.0", Red

Local Order Number 2

English Version: 596-00252

Length L (Imperial)

4.0

Length L (Metric)

101.6

Width W (Imperial)

4.0

Width W (Metric)

101.6

Height H (Imperial)

2.0

Height H (Metric)

50.8

Material

Type 840/926, Polyester (PET), white (WH) UV stable w/ clear Polyester laminate

Material Shortcut

840/926

Adhesive

Acrylic

Halogen free

Yes

Adhesive Operating Temperature

-40°F to +180°F (-40°C to +82°C)

Operating Temperature (Metric) -40°F to +302°F (-40°C to +150°C)

ROHS Complaint Yes

Certification/Specification WEB CSA 66956

UL Recognized (US) Yes

Package Quantity(Imperial) 50

Package Quantity (Metric) 50

Customs Number 3919102055

Labels per Column 1

Labels per Row 1