

Click to Search by Parameter, Diagram, Distributor Inventory, or Keyword

Search by Parameter

select product type

Search

Search by Family Diagram

select product type

Search

Search by Keyword

Search

Search Distributor Inventory

Search

- Back
- Options
 - Print
 - Create PDF
 - (0) Catalog
 - General Specifications
 - Special Order
 - Add to Sample Cart
 - Distributor Inventory
 - Calculate Life
- Print
- Create PDF
- QPC Catalog
- General Specifications
- Special Order
- Add to Sample Cart
- Distributor Inventory
- Calculate Life



305QPC250KA3#

MOTOR RUNIAC

Parts are RoHS compliant

Parts are RoHS compliant

Electrical Specifications

Capacitance: 3 uF

Dissipation Factor: 0.01 Max at 1000 Hz and 25°C

Temperature Coefficient: 400 PPM/°C, -200 PPM/°C, 200 PPM/°C

Ripple Current: 0 at 0 and 0

ESR: - at - and -

Self Inductance: Nanohenries maximum per mm of body length and lead length

dv/dt: V/us

Tolerance: -10 % , +10 %

Temperature Range: -25°C to +85°C

Above 85°C the rated (DC/AC) voltage must be derated at per NIA°C

WVDC: 0 Volts DC

SVDC: N/A Volts DC

VAC: 250 VAC at 70°C

200 VAC at 85°C

Terminal to Terminal Dielectric strength: 1.75 times the rated AC voltage when applied between the terminals for 60 seconds

Terminal to case Dielectric strength: 2000 VAC when applied between the terminals and case for 60 seconds

Insulation Resistance (Terminal to Terminal): 1000 MINIMUM after 100 Volts DC is applied for 60 seconds at 20°C

Reliability: Load Life: 5000 hours at N/A with 0% of rated voltage

Capacitance Change: 0 of initially measured value

D.F. Change: 0 of maximum specified value

I.R. Change: 0 of minimum specified value

Insulation resistance (Terminal to Case): 2000 Megohms MINIMUM after 100 Volts DC is applied for 60 seconds at 20°C

Physical Dimensions

Length (L): 46 mm, 1 mm

Height (H): 24 mm, +/-0.5 mm

Thickness (T): 13 mm, +/-1 mm

Lead Finish: Matte Tin

