



P/N	L(FT)	L(MM)	T
N204-001-BL-UP	1FT	305MM	+15/-15MM
N204-003-BL-UP	3FT	915MM	+25/-25MM
N204-005-BL-UP	5FT	1524MM	+25/-25MM
N204-007-BL-UP	7FT	2134MM	+50/-50MM
N204-010-BL-UP	10FT	3048MM	+50/-50MM
N204-015-BL-UP	15FT	4572MM	+100/-50MM
N204-025-BL-UP	25FT	7620MM	+150/-50MM

WIRE CONNECTION

WIRE COLOR	P1	PAIRS	P2
WHITE/ORANGE	1	———	1
ORANGE	2	———	2
WHITE/GREEN	3	———	3
BLUE	4	———	4
WHITE/BLUE	5	———	5
GREEN	6	———	6
WHITE/BROWN	7	———	7
BROWN	8	———	8

- NOTES:
- CABLE:UTP CAT.6 CABLE.4P\*24AWG(7/0.203)(STRANDED BARE COPPER. INSULATION:HD-PE.OD:0.95±0.05MM)+OUTER JACKET: BLUE PVC.OD:6.2±0.15MM.P/N:(06G-R4P-T24-BL-TPL)
  - CONN.: P1,P2: 8P8C PLUG, LONG BODY, DUBLE LAY. GOLD PLATED 3U", TWO PARTS.P/N:060-R88-T3-24AWG
  - ALL HOOD MOLDED BLUE 60P PVC.
  - CABLE ASS'Y MUST PASS CONTINUITY TEST.



A	INITIAL RELEASE		06/29/11	
REV	DESCRIPTION OF CHANGE		DATE	
TOLERANCE INCHES		M/M		<b>TRIPP-LITE</b>
.X	.015	.30		
.XX	.010	.10		
.XXX	.005	.05		SCALE NONE
DRAWN BY		Tiger		UNIT MM
CHECK BY				⊕ REV A
APPD BY				SHEET 1/1 DWG NO.
				DATE 06/29/11
				TITLE
				8P8C PLUG(90°,UP) TO 8P8C PLUG(180°)
				PART NO. N204-xxx-BL-UP