

## P/N: VSC65-17S

### Copyright

© 2014, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

### Document identity

Publ. No.: VSC65-17S

Release:

Commit: 18096

Language: en-US

Modified: 2014-10-02

Formatted: 2014-10-02

### Corporate Headquarters

FLIR Systems, Inc.  
27700 SW Parkway Ave.  
Wilsonville, OR 97070  
USA  
Telephone: +1-503-498-3547

### Website

<http://www.flir.com>

### Customer support

<http://support.flir.com>

### Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to [exportquestions@flir.com](mailto:exportquestions@flir.com) with any questions.



|                               |  |
|-------------------------------|--|
| Part No.                      | VSC65-17S  |
| <b>General information</b>    |  |
| Short description             | 43 cm (17") stainless steel rigid probe with rotating mirror |
| Compatible main unit          | VS70   |
| Integrated handset            | No   |
| Wireless capabilities         | N/A  |
| Compatible wireless handset   | With optional VST  |
| Compatible detachable cameras | N/A  |
| Warranty                      | 2 years  |
| <b>Camera specifications</b>  |  |
| Articulation                  | No   |
| Diameter                      | 6.5 mm   |
| Resolution                    | VGA (640 x 480 pixels)                                       |
| Probe length                  | 43 cm (17")  |
| Focal length                  | 20–60 mm   |
| Field of view                 | 56°  |
| Imaging sensor                | CMOS   |
| Video format                  | NTSC   |
| Brightness control            | Manual with variable options                                 |
| Lamp type                     | LED  |
| <b>Power system</b>           |  |
| Power requirements            | N/A  |
| <b>Environmental data</b>     |  |
| Operating temperature         | –10 to 50°C (14–122°F)                                       |
| Operating humidity            | 80% maximum  |
| Storage temperature           | –40 to 80°C (–40 to 176°F)                                   |
| <b>Physical data</b>          |  |
| Weight                        | See shipping information                                     |
| Dimensions (H x W x L)        | See shipping information                                     |
| Material                      | Stainless Steel, PC-ABS, rubber hand grip, nylon strap       |
| Color                         | Gray, black  |



## 43 cm (17") stainless steel rigid probe with rotating mirror

**P/N: VSC65-17S**

© 2014, FLIR Systems, Inc.

#VSC65-17S; r. /18096; en-US

| <b>Shipping information</b>      |  |
|----------------------------------|--|
| Packaging type                   | White box with FLIR accessory printing   |
| Packaging contents               | White box with FLIR accessory graphic, camera, camera attachments: rotating mirror |
| Packaging weight                 | 1.75 kg  |
| Packaging dimensions (H x W x L) | 59 cm x 49 cm x 26 cm  |
| Carton weight                    | 8.2 kg   |
| Carton dimensions (H x W x L)    | 46 cm x 32 cm x 40 cm  |
| Carton quantity                  | 4  |
| EAN-13                           | 7332558007716  |
| UPC-12                           | 793950406069   |
| Country of origin                | TW   |
| Tariff code                      | 9013909000   |
| <b>Technical support</b>         |  |
| Website                          | <a href="http://support.flir.com">http://support.flir.com</a>                      |
| E-mail                           | <a href="mailto:T&amp;Msupport@flir.com">T&amp;Msupport@flir.com</a>               |
| Phone                            | 855-499-3662   |
| Repairs                          | <a href="mailto:repair@flir.com">repair@flir.com</a>                               |