

APPLICATOR PARTS LIST

TYPE  
LENGTHWISE  
SPLICE  
"PIGTAIL"

AMP INCORPORATED  
HARRISBURG, PENNA.

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.
1	WIRE CRIMPER <i>453703-9</i>	1	<del>4565003-2</del>	42			
2	INS. CRIMPER			43			
3	ANVIL	1	471359-9	44	Hold Down	1	471716-4
4	ANVIL SPACER			45	Spacer - Stripper	2	377027
5	SHEAR BLADE	1	379063	46	Cleaner <i>2</i>	1	389113
6	REAR SHEAR PLATE	1	385013-4	47			
7	SHEAR BLADE SPACER	2	370954	48			
8	FRONT SHEAR PLATE <i>1-470857-3</i>	1	<del>373285</del>	49			
9	REAR ANVIL SPACER PLT.			50			
10	FRONT ANVIL SPACER PLT.			51			
11	TOOL SPACER	1	372177	52			
12	CRIMP SPACER			53			
13	FRONT STRIP GUIDE	1	373285	54			
14	REAR STRIP GUIDE	1	373285	55			
15	RAM	1	471911	56			
16	TOOL HOLDER			57			
17	ADJ. CRIMP MOUNT			58			
18	ADJ. BLOCK			59			
19	APPLICATOR MOUNT <del>ASSY</del>	1	570656	60			
20	BASE PLATE			61			
21	BASE BLOCK			62			
22	STRIP GUIDE PLATE			63			
23	ANVIL HOLDER	1	370526	64	1" AIR FEED ASSY.	1	690021-1
24	AUX. ANVIL HOLDER	1	377515	65	Tension Adj. Plate	1	374999
25	STRIPPER <i>1</i>	1	388671	MISCELLANEOUS			
26	STRIPPER MOUNT	2	379613	66	Lubricator Ass'y.	1	465184-2
27	RETAINER PLATE	2	372251	67	Synthetic Oil	1	22011-1
28	STRIPPER MOUNT BRACKET			68	Air Blast Ass'y. 455350-1	1	<del>565073-1</del>
29	STRIPPER BUSHING			69	FLEX LUBE	1	811232-1
30	STOCK DRAG	1	375381	70	CLAMP	1	23397-1
31	STOCK DRAG HANDLE	<del>1</del>	<del>375382</del>	71			
32	STOCK DRAG STUD	2	354045-1	72	<del>MECH FEED ASSY</del>	<del>1</del>	<del>692140-2</del>
33	STOCK DRAG SPRING	2	1-23847-1	REVISION RECORD			
34	STOCK DRAG ADJ. SCREW	2	372997	REV.	REVISION RECORD	DATE	BY
35	FEED FINGER HOLDER			A	ITEM E WAS 373401	10-8-70	RB
36	FEED FINGER	1	452817-1	B	REV PER ECN	12-7-70	BUI
37	FEED FINGER TIP			C	REV PER ECN	6-13-72	D.L.
38	FEED FINGER SPACER			D	REV PER ECN	4-3-73	DBS
39	BASE CASTING	1	570238	E	REV PER ECN	4-25-74	DB
40	GUARD <i>457664-1</i>	1	<del>385696</del>	F	0150-6407-95	9/95	LAC
41							

CRIMPING DATA			TERMINALS
TO APPLY TERMINAL			61418-
WIRE SIZE	CRIMP HEIGHT		
18	.044		
16	.052		
14	.064		
CRIMP	SIZE	TYPE	FEED
WIRE	.080	F	
INSUL.			.226
SLEEVED			
INSULATION RANGE		WIRE RANGE	
		18 - 14	
EXPLODED VIEW			
A-6000		A-6000-1	
REMARKS:			
<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">  Mt. Low                 </div> <div style="text-align: center;">  Mt. High                 </div> </div>			
THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INC. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.			
■ DENOTES WEARING PARTS RECOMMEND PURCHASE REPLACEMENT			
THIS APPLICATOR IS TO BE USED ON			
AMP-O-LECTRIC 1-471273-2			
Align. Gage			DIST. 4
SERIAL NO.		DATE SHIPPED	DESIGNED
			11-12-68
CUSTOMER NAME AND ADDRESS			CHK'D.
			11-12-68
			APP'D.
APPLICATOR NUMBER	REV.	SHEET	
F	565904-1	1 of 1	

OK