



P.C.B.-HOLE DRILLINGS

**NOTES:**

1. INSULATOR: PBT GF UL 94 V-0; GREY
2. CONTACTS: COPPER ALLOY
3. PLATING: min. 8µ" HARD GOLD OVER  
min. 50µ" NICKEL
4. PCB-CLIP: COPPER ALLOY  
PCB HOLE  $\phi 2.8 \pm 0.1$  / PCB THICKNESS  $t = 1.6$ mm
5. CONNECTOR IS PART MARKED:  
**121A20839X CONEC Y/WW**

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY, WITHOUT WRITTEN PERMISSION.  
 OWNERSHIP AND COPYRIGHT OF CONEC GmbH  
 DO NOT ALTER CAD DRAWING BY HAND

CONEC CORPORATION  
BRAMPTON, ONTARIO

tolerance



scale:

2:1

material:

SEE NOTES

2002	date	name
drawn	19.03.	Parei
appd.	19.03.	E. Mickenbecker
norm	DIN EN 60603	
d-old		

title:

**MALE CONNECTOR TYPE "B"**  
64 pos. angled  
with clip

dwg no:

AutoCAD 2000

DIN-A

**12K1A188**

3

sh: 1/1

part no:

**121A20839X**

rev.	description	date	name

